



8 Ton Fertilizer Spreader Row Crop Model - 40 inch Frame Clearance



Model F810 - Features

- Variable Rate Ready
- Hydraulic Conveyor Drive
- 20-Inch Dual Stainless-Steel Spinners
- Controlled Spinner Drive
- 40- to 90-Foot Spread Width
- 40-Inch Row Crop Frame Clearance
- 80"- 150" Adjustable Row Crop Wheel Spacing
- Optional 60"-105" Adjustable Walking Tandem
- 40" Row Crop Under Frame/25" Walking Tandem
- Obstruction-Free Interior
- Optional Integrated ISO Rate Controller
- 35-Degree Hopper Slope
- Adjustable Hitch
- Integral Lights
- Optional Hydraulic Fixed Spinner Drive
- Optional Integral 4-Point Scale
- Optional Dual Row Crop Wheels With 60"-134" Spacing
- Optional Roll Tarp
- Multiple Tire Options



agspray.com

CALL FOR OPTIONS AND PRICING

FM 3090

LOFTNESS FERTILIZER SPREADER

Bakersfield, CA
877.724.2236

Columbus, NE
800.274.1025

Dothan, AL
800.227.4098

Fargo, ND
800.373.4084

Hopkinsville, KY
800.637.7172

Mankato, MN
800.722.9376

Newton, KS
800.394.7662

Pasco, WA
800.634.2026

Tempe, AZ
877.974.7166

SPECIFICATIONS

Spread Pattern (Dual)(Hydraulic)	40-90 ft.	
Spread Pattern (Dual)(Mechanical)	50 ft.	
Hopper Capacity-Struck	241 cu. ft.	
Hopper Capacity-Heaped	266 cu. ft.	
Weight-Empty	5540 lbs.	
Max Gross Weight	20,000 lbs.	
Overall Length	196 in.	
Frame/Crop Clearance	40 in.	
Overall Width	92 -168 in.	
Overall Height	120 in.	
Hopper Length	119 in.	
Hopper Width	92 in.	
Hopper Height	56 in.	
Standard Tires	380/90-R46	
Axles/Suspension	6 x 6 in. - infinitely adjustable from 80 - 150 in.	
Frame	6 x 3 in. x 10 ga. rectangular tubing	
Hitch	¾ in., hot-rolled sheet, channel-formed	
Drawbar	Bolt-in, adjustable position	
Hopper	12-gauge, 409 stainless steel	
Skid	12-gauge, 409 stainless steel	
Gate	7-gauge, 409 stainless steel	
Conveyor Chain	7-in. wide, 304 stainless steel with 1-in. x 1-in. mesh	
Spinner Dish	19" dia. 7 gauge, 409 stainless steel	

OPTIONS

Conveyor Drive	Hydraulic Drive (Standard) Mechanical Drive (Optional) Two-speed axle-driven transmission Hydraulic engage/disengage from cab Stainless steel chains
Spinner Drive	Hydraulic drive (Standard) 540 rpm PTO (Optional) 540/1000 rpm dual-drive PTO (Optional)
Tires	480/80-R42 or 320/90-R50
Roll Tarp	Optional



agspray.com